

* ALL SPRING RATES ARE
(lbs./in.)

SPRING RATE SETUP CHART

FOR 3S & 4S
ARRMA

FRONT

	(P) PRIMARY 19mm FRONT SPRINGS	(S) SECONDARY 51mm FRONT SPRINGS	SOFT (OPTION 1)	MEDIUM (STOCK)	FIRM (OPTION 2)
	7.0	9.0	11.0		
SOFT (OPTION 1)	5.5	3.1 (lbs./in.)	3.4 (lbs./in.)	3.7 (lbs./in.)	
MEDIUM (STOCK)	7.0	3.5 (lbs./in.)	3.9 (lbs./in.)	4.3 (lbs./in.)	
FIRM (OPTION 2)	8.5	3.8 (lbs./in.)	4.4 (lbs./in.)	4.8 (lbs./in.)	

REAR

	(P) PRIMARY 19mm REAR SPRINGS	(S) SECONDARY 65mm REAR SPRINGS	SOFT (OPTION 1)	MEDIUM (STOCK)	FIRM (OPTION 2)
	7.0	9.0	11.0		
SOFT (OPTION 1)	4.0	2.5 (lbs./in.)	2.8 (lbs./in.)	2.9 (lbs./in.)	
MEDIUM (STOCK)	5.5	3.1 (lbs./in.)	3.4 (lbs./in.)	3.7 (lbs./in.)	
FIRM (OPTION 2)	7.0	3.5 (lbs./in.)	3.9 (lbs./in.)	4.3 (lbs./in.)	

* Combined Spring Rate: This number is the combined Spring Rate and as the top spring fully compresses, the bottom spring takes over for impact absorption. Spring Rate then is the bottom single Spring Rate.

OPTIMUM SOFT DUAL RATE
 OPTIMUM MEDIUM DUAL RATE
 OPTIMUM FIRM DUAL RATE